

> Super Fast Chargers

It charges most batteries in 1 to 4 hours. They also offer multiple levels of safety protection and many convenient features, such as LED displays and worldwide use plugs.

BC-0905A

Charges:


1 or 4 × AA

1 or 4 × AAA

Ni-MH



Flip plug



*Different plug models for different countries



SPECIFICATIONS

Input: 100-240V~50/60Hz

Output: AA: 1000mA (1- 2 pcs),

500mA (3-4 pcs)

AAA: 600mA (1- 2 pcs),

300mA (3-4 pcs)

MAIN FEATURES

- **4 Independent Charging Channels**
- **6 Level Charge Protections**
 - ΔV Cut Off
 - Timer Control Protection
3.5 hours(1-2cells) or 7 hours(3-4cells)
 - Over Temperature Protection
 - Reverse Polarity Protection
 - Over Current and Short Circuit Protection
 - Defective and Non-rechargeable Battery Detection
- **Trickle Charge**
- **Switch and Match Plugs**
- **LED Indicators**

Red	Charging
Flashing	Defective or non-rechargeable batteries / Short circuit
Green	Fully charged / trickle

CHARGING TIMES

Type of Battery	Charging Times (Appr.)	
	1-2 Cells	3-4 Cells
Ni-MH AA 2700 mAh	3 h	6 h
Ni-MH AA 2000 mAh	2.5 h	4.5 h
Ni-MH AA 1500 mAh	2 h	3.5 h
Ni-MH AAA 800 mAh	100 min	3 h
Ni-Cd AA 1000 mAh	70 min	2 h
Ni-Cd AAA 300 mAh	40 min	70 min

AVAILABLE COLORS

Black

BARCODE

BC-0905A-UK-0



PACKAGING



UK

Blister		
Plug:	TUV	UK
Weight(g)	153	144
Dimensions(W)x(H)x(D)(mm)	125x205x70	125x205x70
Inner Carton		
Packs / Inner ctn	16	16
Net Weight(kg)	2.45	2.3
Gross Weight(kg)	3	3
Dimensions(L)x(W)x(H)(cm)	48.5x22.5x27	48.5x22.5x27
Outer Carton		
Packs / Carton	32	32
Net Weight(kg)	4.9	4.8
Gross Weight(kg)	6.4	6.3
Dimensions(L)x(W)x(H)(cm)	51x 47 x 29	50 x 47 x 29
Volume(cbm)	0.0682	0.0682